

➔ BUSINESS SHREDDER IDEAL 3105

INNOVATIVE HIGH CAPACITY OFFICE SHREDDERS WITH A3 FEED OPENING

"SPS" - (Safety Protection System) package: electronically controlled, transparent safety flap in the feed opening as additional safety element; "EASY_SWITCH" - intelligent control element indicating the operational status of the shredder with varying colour codes and back-lit symbols; automatic reverse and power cut-off (avoids paper jams); automatic stop if the shred bag is full; electronic door protection via a magnetic proximity switch; double motor protection; energy-saving mode after 1 hour | photo cell controlled automatic start and stop | "ECC" - Electronic Capacity Control - indication of the used sheet capacity during shredding process | automatic oil injection on the cutting shafts during shredding operation for constantly high shred performance | convenient 310 mm feed opening for A3 (lengthwise) or A4 (lengthwise and widthwise) | high quality paper clip proof² cutting shafts from special hardened steel | models IDEAL 3105 and IDEAL 3105-C/C suitable for safe shredding of CDs | 5 years guarantee² on the cutting shafts | quiet but powerful 1600 Watt single phase motor for continuous operation | sturdy chain drive and dust-proof gear box housing | high-quality wooden cabinet, mobile on castors | plastic bag suspension with pull-out mechanism on wheels for easy removal of the full bag (approx. 180 litres volume); model IDEAL 3105-SM/C comes with 100 litres shred bin

Power connection³: 230 V / 50 Hz / 1~, Dimensions (H x W x D): 1020 x 548 x 590 mm, Weight: 102 kg



"ECC" CONTROL



..ECC" - Electronic Capacity Control: for continuous feeding without creating paper jams the used sheet capacity is indicated during the shredding process.

➔ IDEAL 3105

Shred width	6 mm
Sheet capacity ¹	50-55 42-47
Security level	2
Feed opening	310 mm
Motor capacity	1600 Watt

➔ IDEAL 3105-C/C

Particle size	4 x 40 mm
Sheet capacity ¹	40-45 34-39
Security level	3
Feed opening	310 mm
Motor capacity	1600 Watt

➔ IDEAL 3105-C/C

Particle size	2 x 15 mm
Sheet capacity ¹	25-30 21-26
Security level	4
Feed opening	310 mm
Motor capacity	1600 Watt

➔ IDEAL 3105-SM/C

Particle size	0.8 x 5 mm
Sheet capacity ¹	11-12 9-10
Security level	"Level 6"
Feed opening	310 mm
Motor capacity	1600 Watt



I.T.E. Listed 802 D

¹ A4 paper, 70 g/m² | 80 g/m²

² 3105-SM/C 0.8 x 5 mm:

Paper clips and staples have to be removed before shredding.

Guarantee 1 year.

³ other voltages available

➔ BUSINESS SHREDDER IDEAL 3105 + ACCESSORIES

MODEL	ARTICLE NO.	EAN CODE
IDEAL 3105, 6 mm 230 V, 50 Hz*	31056111	4019364619311
IDEAL 3105 -C/C, 4 x 40 mm 230 V, 50 Hz*	31059111	4019364619519
IDEAL 3105 -C/C, 2 x 15 mm 230 V, 50 Hz*	31051111	4019364619410
IDEAL 3105 -SM/C, 0.8 x 5 mm 230 V, 50 Hz*	31057111	4019364619618
Plastic bags for IDEAL 3105 with bag suspension (50 pieces per packing unit)	9000410	4019364940705
Plastic bags for IDEAL 3105 with shred bin (50 pieces per packing unit)	9000037	4019364940606
Shredder oil for IDEAL 3105 (5 x 1 litre per packing unit)	9000620	4019364950858

* other voltages available

TRANSPARENT SAFETY FLAP




The safety flap in the feed opening is an additional safety element to keep fingers, ties or other objects away from the cutting shafts.

"EASY_SWITCH"



Intelligent multifunction switch element with integrated optical signals for the operational status.

AUTOMATIC OIL INJECTION



The automatic oil injection system lubricates the cutting shafts when shredding and guarantees a constantly high shred performance.

PLASTIC BAG SUSPENSION



The plastic bag suspension on wheels allows an easy and convenient removal of the full shred bag.