

Power guillotine with manual spindle clamp



IDEAL 4810-95

| | |
|------------------------|---------------------|
| Cutting length | 475 MM |
| Cutting height | 80 MM |
| Table depth | 458 MM |
| Narrow cut | 30 MM |
| Power supply | 230 V/50 Hz/1~* |
| Motor performance | |
| (Input capacity) | 1.1 KW |
| Dimensions (H x W x D) | 1360 X 755 X 970 MM |
| Weight | 194 KG |

TECHNICAL DETAILS AND FEATURES

- electro-mechanical blade drive
- manual spindle clamp, guided on both sides, with large hand wheel
- spindle guided backgauge with hand crank
- measuring scale (mm/inches), located on front table
- two side lays each on front and rear tables
- solid steel blade carrier and adjustable blade guides
- adjustable backgauge with narrow separations and plastic gliders
- high quality blade made from "Solingen steel"
- complete with stand and storage shelf

SAFETY FEATURES

- safety guards on front and rear tables
- patented IDEAL safety drive
- electronically controlled true two-hand operation
- automatic blade return
- disc brake for instant blade stop
- main switch, safety lock with key
- 24 Volt controls (low voltage)
- blade changing device with covered cutting edge
- blade depth adjustment from the outside of the machine
- cutting aid for aligning the paper
- safety tested by major independent safety laboratories and complies with the European "CE" standards

* other voltages available

Power guillotine with programmable "EP" backgauge control module



IDEAL 4810-95 EP

| | |
|---------------------------------------|---------------------|
| Cutting length | 475 MM |
| Cutting height | 80 MM |
| Table depth | 450 MM |
| Narrow cut | 35 MM |
| Power supply | 230 V/50 Hz/1~* |
| Motor performance (Input capacity) | |
| · Blade drive | 1.1 KW |
| · Backgauge drive | 0.1 KW |
| Dimensions (H x W x D) | 1360 x 755 x 970 MM |
| Weight | 200 KG |

TECHNICAL DETAILS AND FEATURES

- electro-mechanical drive of blade and backgauge
- manual spindle clamp, guided on both sides, with large hand wheel
- power backgauge with fully programmable "EP" backgauge control module, digital measurement readout and electronic hand wheel
- optical cutting line
- two side lays each on front and rear tables
- solid steel blade carrier and adjustable blade guides
- adjustable backgauge with narrow separations and plastic gliders
- high quality blade made from "Solingen steel"
- complete with stand and storage shelf

SAFETY FEATURES

- safety guards on front and rear tables
- patented IDEAL safety drive
- electronically controlled true two-hand operation
- automatic blade return
- disc brake for instant blade stop
- main switch, safety lock with key
- 24 Volt controls (low voltage)
- blade changing device with covered cutting edge
- blade depth adjustment from the outside of the machine
- cutting aid for aligning the paper
- safety tested by major independent safety laboratories and complies with the European "CE" standards

BACKGAUGE CONTROL MODULE

- digital display for measurement readout in cm or inches (display accurate to 1/10 mm or 1/100 inch)
- 10-button key pad for presetting of measurement
- memory key for repeat cuts
- programmable "EP" backgauge control module for 9 programs with 9 steps in each program (up to 9 repeat cuts can be integrated into a program as one single program step)
- setting of program steps via "Start" button
- "SET" function key for reference measurement
- programmable EJECT function - for pushing out the paper
- two programmable keys for quick setting of frequently needed measurements
- self-diagnosis system with error indication on display

* other voltages available